

SAE SPUDS		SIZE DESIGNATOR																															
		SAE EQUIVALENT																															
SAE		2		3		4		5		6		8		10		12		14		16		20		24		32							
SFI #		OAL	THR'D	OAL	THR'D	OAL	THR'D	OAL	THR'D	OAL	THR'D	OAL	THR'D	OAL	THR'D	OAL	THR'D	OAL	THR'D	OAL	THR'D	OAL	THR'D	OAL	THR'D	OAL	THR'D						
SAE MALE ADJ. ANVILS	J514	.610	1/16 - 24	.610	3/8 - 24	.700	1/16 - 20	.700	1/2 - 20	.770	1/16 - 18	.880	1/4 - 16	1.020	1/8 - 14	1.160	1 1/16 - 12	1.160	1 3/16 - 12	1.160	1 5/16 - 12	1.160	1 7/8 - 12	1.160	1 7/8 - 12	1.160	2 1/2 - 12						
	101																																
SAE MALE ADJ. ANVILS	J1453	NA		NA		.810	1/16 - 20	NA		.880	1/16 - 18	1.030	1/4 - 16	1.190	1/8 - 14	1.330	1 1/16 - 12	NA		1.360	1 3/16 - 12	1.360	1 3/8 - 12	1.360	1 7/8 - 12	NA							
	102																																
SAE MALE O-RING	J514	.297	1/16 - 24	.297	3/8 - 24	.360	1/16 - 20	.360	1/2 - 20	.391	1/16 - 18	.438	1/4 - 16	.500	1/8 - 14	.594	1 3/16 - 12	.594	1 3/16 - 12	.594	1 5/16 - 12	.594	1 5/8 - 12	.594	1 7/8 - 12	.594	2 1/2 - 12						
	201																																
SAE FEMALE O-RING	J514	.468	1/16 - 24	.468	3/8 - 24	.547	1/16 - 20	.547	1/2 - 20	.609	1/16 - 18	.668	1/4 - 16	.781	1/8 - 14	.906	1 1/16 - 12	.906	1 1/16 - 12	.906	1 5/16 - 12	.906	1 5/8 - 12	.906	1 7/8 - 12	.906	2 1/2 - 12						
	202																																
MALE 37° JIC	J514	.448	1/16 - 24	.479	3/8 - 24	.550	1/16 - 20	.550	1/2 - 20	.556	1/16 - 18	.657	1/4 - 16	.758	1/8 - 14	.864	1 1/16 - 12	.890	1 3/16 - 12	.911	1 5/16 - 12	.958	1 5/8 - 12	1.083	1 7/8 - 12	1.333	2 1/2 - 12						
	301																																
37° BULKHEAD	J514	1.110	1/16 - 24	1.110	3/8 - 24	1.200	1/16 - 20	1.200	1/2 - 20	1.280	1/16 - 18	1.504	1/4 - 16	1.580	1/8 - 14	1.750	1 1/16 - 12	1.750	1 1/16 - 12	1.750	1 5/16 - 12	1.800	1 5/8 - 12	1.810	1 7/8 - 12	2.090	2 1/2 - 12						
	302																																
FEMALE 37° SWIVEL	J514	NA		NA		.427	1/16 - 20	NA		.457	1/16 - 18	.557	1/4 - 16	NA		.680	1 1/16 - 12	NA		.740	1 5/16 - 12	NA		.740	1 7/8 - 12	NA							
	303																																
MALE O-RING FACE SEAL	J1453	NA		NA		.386	1/16 - 18	NA		.441	1 1/16 - 16	.557	1 1/16 - 16	.610	1-14	.670	1 1/16 - 12	NA		.689	1 7/16 - 12	.689	1 11/16 - 12	.689	2-12	NA							
	401																																
FEMALE O-RING FACE SEAL	J1453	NA		NA		.427	1/16 - 18	NA		.457	1 1/16 - 16	.557	1 1/16 - 16	.557	1-14	.680	1 3/16 - 12	NA		.740	1 7/16 - 12	NA		.740	2-12	NA							
	402																																

NPTF SPUDS		EQUIVALENT TO SCHED 40 OR SCHED 80, 3000 PSI MAX.															
		2		4		6		8		12		16		20		24	
SFI #		1/8 NPTF	1/4 NPTF	3/8 NPTF	1/2 NPTF	3/4 NPTF	1 NPTF	1-1/4 NPTF	1-1/2 NPTF								
MALE NPTF	34769	*	1/8 - 27	*	1/4 - 18	*	3/8 - 18	*	1/2 - 14	*	3/4 - 14	*	1-11 1/2	*	1 1/2 - 11 1/2	*	1 7/8 - 11 1/2
	501																
FEMALE NPTF	34769	*	1/8 - 27	*	1/4 - 18	*	3/8 - 18	*	1/2 - 14	*	3/4 - 14	*	1-11 1/2	*	1 1/2 - 11 1/2	*	1 7/8 - 11 1/2
	502																

BARB TYPE SPUDS		TUBE O.D.							
		3	4	5	6	7	8	9	10
SFI #		3/16	1/4	5/16	3/8	7/16	1/2	9/16	5/8
ROLLED HOSE BEAD	J962	LENGTH AS REQUIRED							
	601								
MACHIN ED HOSE BEAD	J962								
	602								